

30V N-Channel MOSFETs

General Description


These N-Channel enhancement mode power field effect transistors are using trench - technology. This advanced technology is designed to minimize on-state resistance, provide superior switching performance, and withstand high energy pulse in the avalanche period. These devices are well suited for high efficiency fast switching applications.

$V_{(BR)DSS}$	$R_{DS(ON)}$	I_D
30V	18m Ω	18A

Features

- Fast switching
- Improved dv/dt capability
- Green Device Available

Power PAK 3333 Pin Configuration



Applications

- MB / VGA / Vcore
- Load Switch
- Hand-Held Instrument

Absolute Maximum Ratings ($T_J=25^{\circ}\text{C}$, unless otherwise noted)

Symbol	Parameter		Value	Unit
V_{DS}	Drain-Source Voltage		30	V
V_{GS}	Gate-Source Voltage		± 20	
I_D	Drain Current-Continuous ^A	$T_A = 25^{\circ}\text{C}$	8	A
		$T_A = 70^{\circ}\text{C}$	6	
		$T_C = 25^{\circ}\text{C}$	18	
		$T_C = 100^{\circ}\text{C}$	10	
I_{DM}	Drain Current-Pulsed ^{A, B}	$T_A = 25^{\circ}\text{C}$	50	W
I_{AS}	Non-repetitive Avalanche Current ^E		15	
E_{AS}	Single Pulse Drain-to-Source Avalanche Energy ^E		11.25	mJ
P_D	Maximum Power Dissipation	$T_A = 25^{\circ}\text{C}$	3.1	W
		$T_C = 25^{\circ}\text{C}$	12.5	
T_J, T_{STG}	Operating and Storage Temperature Range		-55 to +150	$^{\circ}\text{C}$

Thermal Characteristics

Symbol	Parameter	Conditions	Value	Unit
$R_{\theta JA}$	Junction-to-Ambient ^C	Steady State	40	$^{\circ}\text{C/W}$
$R_{\theta JC}$	Junction-to-Case	Steady State	10	$^{\circ}\text{C/W}$